





TECHNICAL SPECIFICATIONS

SAMTAT GS TIPPER WITH AUXILIARY GEARBOX

Engine Power	85 kW (115 hp) @ 2,600 rpm
Torque	400 Nm @ 1500 rpm
Engine Description	SLT4 BS IV 3,455 cc
Eligille Description	ŕ
	4 Cylinder in-line Common Rail Direct Injection
	Diesel Engine with Turbocharger with Intercooler
Transmission	SMT40S5
	5 Speed (5 Forward and 1 Reverse)
Clutch	310 mm Dry Single Plate with Diaphragm Spring
	with Hydraulic Booster
Suspension	Semielliptical type Multileaf Spring
	with Shock Absorber
Steering	Power Steering
GVW	9,500 kg
Brakes	Dual Circuit, Full S Cam Air Brakes
Tyre Size	8.25 X 16 - 16 PR
Rear Axle	Heavy duty 13"
Wheel Base	2,815 mm
PTO	Pnuematically Operated PTO
Cargo Body Dimensions	3,305 x 1,900 x 720 mm
Internal (length x width x height)	
Floor Thickness	5 mm
Side Wall Thickness	4 mm
Upper Body Tipping Kit	Wipro WID 16 (Double Jack)
Load Body Capacity	4.5 cubic meter

BS-III variant available for export only

Disclaimer: Above specifications may change without any prior notice, as per the company's policy of continuous improvement of its products/services.



Ph.: +91 172-2647700-10

Website: www.smlisuzu.com E-mail: salesadm@smlisuzu.com

WHY CHOOSE SML?

- Wide & Far Reaching Network.
- Excellent Service Support.
- Trustworthy and be assured that your vehicle is in the safe hands when it comes to service.
- Easy Available of Spares.
- Easy Finance Available from all leading Banks and financial lending institutions.

SALIENT FEATURES

- · Corrosion resistant painted steel floor (Stainless Steel / Aluminium checkered lining option available)
- · All components pre-treated for longer life
- High quality poly-urethane paint used.
- Small and rugged design for easy operation.
- · High gradeability for better climbing.
- · Auto-tail gate system (optional).

WARRANTY

As per standard company policy.



AUTHORISED DEALER